

Parameter

Bundle Extractor model	25T	25T	35T	35T	45T	45T	45T
☞ Maximum bundle weight (kg)	25000	25000	35000	35000	45000	45000	45000
☞ Maximum bundle length without extension (mm)	6000	8000	6000	8000	8000	10000	9000
☞ Extractor length without extension (mm)	7400	9400	7600	9600	9600	11600	10600
☞ Extractor length without extension (mm)	7000	9000	7000	9000	9000	11000	10000
☞ Extractor length with front extension (mm)	8400	10400	8600	10600	9600	12600	11600
☞ Maximum bundle length with front and rear extensions (mm) - optional	9000	-	9000	-	11000	-	12000
☞ Extractor length with front and rear extensions (mm)	10400	-	11600	-	12600	-	13600
☞ Maximum bundle diameter of the standard lifting frame (mm)	1600	1600	1600	1600	2000	2000	2000
☞ Other available lifting frame sizes (mm) - optional	2000/2250	2000/2250	2000/2250/2500	2000/2250/2500	2250/2500/2750/3000	2250/2500/2750/3000	2250/2500/2750/3000
☞ Operating weight (kg)	5500	6000	7000	7500	9000	9600	13500
☞ Diesel engine power (KW)	36	36	36		36	36	36
☞ "Standard hydraulic pressure (bar)	180	180	180		180	180	180
☞ Maximum winch pulling force (ton)	30	30	45	45	60	60	60/85
Bundle Extractor model	65T	65T	85T	85T	105T	125T	
☞ Maximum bundle weight (kg)	65000	65000	85000	85000	105000	125000	
☞ Maximum bundle length without extension (mm)	9000	12000	9000	12000	12000	custom	
☞ Extractor length without extension (mm)	10600	13600	10800	13800	14000	-	
☞ Extractor length without extension (mm)	10000	13000	10000	13000	-	-	
☞ Extractor length with front extension (mm)	11600	14600	11800	14800	-	-	
☞ Maximum bundle length with front and rear extensions (mm) - optional	12000	-	12000	-	-	-	
☞ Extractor length with front and rear extensions (mm)	13600	-	13600	-	-	-	
☞ Maximum bundle diameter of the standard lifting frame (mm)	2000	2000	2500	2500	3000	-	
☞ Other available lifting frame sizes (mm) - optional	2250/2500/2750/3000	2250/2500/2750/3000	2000/2750/3000/3500	2000/2750/3000/3500	3500	-	
☞ Operating weight (kg)	14500	14500	16400	17000	23200	-	
☞ Diesel engine power (KW)	36	36	36	36	36	-	
☞ "Standard hydraulic pressure (bar)	180	180	180	180	180	-	
☞ Maximum winch pulling force (ton)	60/85	60/85	85	85	100	-	